

Studio Monitors

TRUTH

B2030A

High-Resolution, Active 2-Way
Reference Studio Monitor

- Ultra-linear frequency response from 50 Hz to 21 kHz with individual frequency diagrams
- Built-in 125-Watt Bi-amp module with enormous power reserve
- Ultra high-resolution ferrofluid-cooled tweeter
- Long-throw 6 ¾" woofer with special polypropylene diaphragm and deformation-resistant aluminum die-cast chassis
- Controlled dispersion characteristics and extremely large "sweet spot" owing to the unique BEHRINGER wave guide technology
- Active crossover network with 4th order Linkwitz-Riley filters
- Adjustable to a wide range of acoustic conditions and subwoofer operation
- Separately controlled limiter for low and high frequency overload protection
- Magnetic shielding allows placement near computer monitors
- Servo-balanced inputs with XLR and ¼" TRS connectors
- 3-Year Warranty Program*
- Designed and engineered in Germany



Our TRUTH B2030A monitors have been so wildly successful, that we've sold thousands upon thousands of them to some of the most critical ears on the planet. Due to their high-resolution performance, B2030A active 2-way reference studio monitors are perfect for near-field monitoring applications – from small mixing environments to multi-channel surround setups.




When it comes to your studio recordings, you want honesty. In fact, considering how important your art is, you should demand it! That's why we designed the B2030A Active 2-Way Reference Monitor to speak nothing but the TRUTH. The B2030A boasts big power, 125 Watts of bi-amplified output to an ultra-responsive, long-throw 6.75" polypropylene woofer, which provides tight and accurate bass – and a high-resolution, ferrofluid-cooled tweeter for crystal-clear highs. And although it was designed for the studio, where every note you play or sing is always "under the microscope", the B2030A makes an absolutely fantastic addition to your stereo or video surround system!

Studio Monitors

TRUTH B2030A

High-Resolution, Active 2-Way
Reference Studio Monitor



Bi-Amplification - The Path to Absolute Signal Integrity

With its 125 ultra-clean Watts of output through separately-powered drivers, courtesy of true bi-amping (2 amplifiers per speaker system), the B2030A delivers high-resolution sound that really brings out the best in your music. While some of our competitors apply simple passive crossovers, which inaccurately separate the frequency spectrum and degrade driver performance, **BEHRINGER** has gone the extra mile – driving each woofer and tweeter with a separate amplifier for the utmost in signal integrity.

Custom-Engineered Transducers

Powerful amplifiers coupled with state-of-the-art technology sure sounds impressive – but what about the part of the system you actually hear? Our LF (Low Frequency) and HF (High Frequency) transducers are designed specifically for each application – it's what sets us apart from the competition. When you buy a TRUTH B2030A active monitor, you can rest assured the transducers inside have been engineered to perform flawlessly with every other element for truly professional results. As a result, the B2030A provides ruler-flat frequency response from 50 Hz - 21 kHz, with tight and accurate low end, articulately-detailed mids and crystal-clear highs.



Gloriously-Wide "Sweet Spot"

The B2030A's HF (High Frequency) content comes courtesy of an ultra-high resolution 1.0" ferrofluid-cooled tweeter mounted on our proprietary wave guide. While some of our competitor's studio monitors have a highly-focused "sweet spot" (the optimal listening position for a pair of loudspeakers), our wave guide is designed to create a much more generous, broader listening zone. That means you are free to move around inside the stereo image to find the ideal spot in the mix for subtle instrument or effects placement opportunities.

Studio Monitors

TRUTH


B2030A

High-Resolution, Active 2-Way
Reference Studio Monitor

Suited for All Placements

The ideal environment for listening is a room that is “flat,” neither too reflective (echoes) nor too absorptive (where the sound is muffled). But since all rooms are not the same acoustically, all TRUTH monitors come equipped to function in a wide variety of environments. Rear panel filter switches are provided to adapt the monitor’s low- and high-frequency characteristics for optimal performance – specifically for your listening environment.

Monitor placement is also critical. Ideally, all loudspeakers should be placed away from walls to ensure proper bass response. The B2030A features a set of Room Compensation switches so you can place it against walls, or even in corners. Walls tend to enhance low-frequency content, and corners exaggerate bass even more, but your B2030A TRUTH can be custom-tailored to provide honest bass response for your situation, with the simple flick of a switch or two.



Ready for Your Input

The B2030A is equipped with servo-balanced inputs on XLR and ¼" TRS connectors to handle a variety of audio sources. Thanks to its compact size and magnetic shielding, the TRUTH B2030A can be placed near video monitors, computer displays or digital audio workstations.

Studio Monitors

TRUTH B2030A

High-Resolution, Active 2-Way
Reference Studio Monitor

Hear the TRUTH

We will skip all all the technical jargon, but hearing the TRUTH will make you a believer. Thanks to its state-of-the-art wave guide technology, custom-designed LF and HF transducers, 125-Watt bi-amplified output and more, the TRUTH B2030A outperforms everything in its class. Compare the B2030A to the competition and finally, hear the TRUTH!



You Are Covered

We always strive to provide the best possible Customer Experience. Our products are made in our own MUSIC Group factory using state-of-the-art automation, enhanced production workflows and quality assurance labs with the most sophisticated test equipment available in the world. As a result, we have one of the lowest product failure rates in the industry, and we confidently back it up with a generous [Warranty program](#).

Studio Monitors

TRUTH B2030A

High-Resolution, Active 2-Way
Reference Studio Monitor



Studio Monitors

TRUTH B2030A


High-Resolution, Active 2-Way
Reference Studio Monitor



Studio Monitors

TRUTH B2030A

High-Resolution, Active 2-Way
Reference Studio Monitor



For service, support or more information contact the BEHRINGER location nearest you:

Europe
MUSIC Group Services UK
 Tel: +44 1562 547 100
 Email: CARE@music-group.com

USA/Canada
MUSIC Group Services NV Inc.
 Tel: +1 702 963 1300
 Email: CARE@music-group.com

Japan
MUSIC Group Services JP K.K.
 Tel: +81 3 5833 9121
 Email: CARE@music-group.com

MUSIC Group accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph, or statement contained herein. Technical specifications, appearances and other information are subject to change without notice. All trademarks are the property of their respective owners. MIDAS, KLARK TEKNIK, LAB GRUPPEN, LAKE, TANNÖY, TURBOSOUND, TC ELECTRONIC, TC HELICON, BEHRINGER, BUGERA and COOLAUDIO are trademarks or registered trademarks of MUSIC Group IP Ltd.
 © MUSIC Group IP Ltd. 2018 All rights reserved.

