



# kramer

## C-HM/HM

Cable HDMI de Alta Velocidad PREMIUM

| HDMI | 4K/60 UHD (4:2:0) | 4K/60 UHD (4:4:4)  
| 4K HDR



El cable Kramer C-HM/HM es la elección perfecta si necesita un cable HDMI de altas prestaciones. Admite señales de hasta 4K@60Hz (4:4:4), Profundidad de Color, x.v.Color™, Lip Sync, 7.1 PCM, Dolby TrueHD, DTS-HD y CEC

## FEATURES

**Prestaciones de Calidad** - Los cables Kramer HDMI proporcionan un enlace sin compresión digital entre los equipos de consumo tales como reproductores DVD, decodificadores y monitores de audio/vídeo como pantallas de plasma para Televisores de alta definición

**Máx. Resolución** - 4K@60Hz (4:4:4)

**Conectores Alta Calidad** - Conectores dorados 24K para resistir la corrosión, y ofrecer la mejor conectividad posible

**Conectores K-Lock Resistentes a la Extracción** - Proporcionan 15lbs de fuerza de extracción para una conexión sin deslizamiento

**Premium certified (up to 15ft)**

**Variada Selección de Longitudes** - Disponible en versiones de 0.9 a 15.2m (3, 6, 10, 15, 25, 35 y 50 pies)



# kramer

## TECHNICAL SPECIFICATIONS

---

Video	Max Resolution for 3–15ft (.9–4.6m) lengths: 4K@60Hz (4:4:4) Max Resolution for 25–35ft (7.6–10.7m) lengths: 4K@60 (4:2:0) Max Resolution for 50ft (15.2m) lengths: 1080p Max Data Rate for 3–15ft (.9–4.6m) lengths: 18 Gbps Max Data Rate for 25–35ft (7.6–10.7m) lengths: 8.91 Gbps Max Data Rate for 50ft (15.2m) lengths: 4.95Gbps Supported Color Spaces: RGB, YCbCr, xvYCC, Adobe sRGB, sYCC601, BT.2020 HDMI Compliance: HDR, HDCP 2.2, EDID and CEC
Audio	Supported Audio Formats: Dolby Digital Plus™, Dolby TrueHD™, DTS–HD Master Audio™, DVD Audio, SA–CD
PHYSICAL	HDMI Source: On a male HDMI type A, 24K gold–plated K–Lock connector HDMI Display: On a male HDMI type A, 24K gold–plated K–Lock connector
CONDUCTORS	Material: Tinned Copper/Bare Copper 3–35ft (.9–10.7m) lengths: 28AWG (7/0.127) 50ft (15.2m) lengths: 26AWG (7/0.160)
SCREENING	Type: Triple shielding
JACKET	Material: PVC Color: Gray Diameter for 3–35ft (.9–10.7m) lengths: 6.50 ± 0.15mm Diameter for 50ft (15.2m) lengths: 9 ± 0.25
MECHANICAL	Cable Bending Radius for 3–35ft (.9–10.7m) lengths: 60mm Cable Bending Radius for 50ft (15.2m) lengths: 90mm
ELÉCTRICA	Temperature Rating: 80°C Voltage Rating: 30V Conductor Resistance – 28AWG: 237.25Ω/km Conductor Resistance – 26AWG: 148Ω/km MAX. at 20°C (68°F)
STANDARDS COMPLIANCE	Safety: Flammability Rating – CL3/FT4 Environmental: RoHS 2011/65/ EU





# kramer

## CONFIGURATIONS

C-HM/HM-3	Cable HDMI de Alta Velocidad
C-HM/HM-6	Cable HDMI de Alta Velocidad
C-HM/HM-10	Cable HDMI de Alta Velocidad
C-HM/HM-15	Cable HDMI de Alta Velocidad
C-HM/HM-25	Cable HDMI de Alta Velocidad
C-HM/HM-35	Cable HDMI de Alta Velocidad
C-HM/HM-50	Cable HDMI de Alta Velocidad

