



Introduction

The Atlona AT-OME-RX11 is an HDBaseT receiver for video up to 4K/60 4:2:0, plus embedded audio, control, and Ethernet over distances up to 330 feet (100 meters). Part of the Omega™ Series of integration products for modern AV communications and collaboration, the OME-RX11 is HDCP 2.2 compliant and receives RS-232 and IP control signals. Additionally, this receiver features two-channel audio de-embedding to a balanced analog audio output. The OME-RX11 is locally powered, and can deliver Power over Ethernet (PoE) over HDBaseT to an Atlona Omega Series, HDVS-200 Series, or AT-UHD-EX-100CE-TX-PD transmitter.

The OME-RX11 incorporates many popular integration convenience features, while delivering excellent performance and value for 4K presentation applications. The Ethernet port on the OME-RX11 is for IP pass-through with the transmitter.

Applications

- **Complete system integration**
The OME-RX11 and an Omega Series switcher together provide a comprehensive and cost-effective integration solution for meeting rooms and other AV presentation spaces..
- **Larger system applications**
The OME-RX11 offers a new option for legacy Atlona transmitters and switchers with HDBaseT outputs, to provide audio de-embedding for feeding into an amplifier and speakers.

Key Features

Video, audio, power, and data over category cable utilizing HDBaseT technology

- Receives up to 330 feet (100 meters) @ 1080p with CAT5e/6 or 4K/UHD using CAT6a/7 cable.
- Uses easy-to-integrate category cable for low-cost, reliable system installation.

4K/UHD capability @ 60 Hz with 4:2:0 chroma subsampling

- Compatible with sources up to 4K/60 4:2:0 and 4K/30 4:4:4.
- Supports HDMI data rates up to 10 Gbps from PCs, media players, and Ultra HD Blu-ray players.

HDCP 2.2 compliant

- Adheres to latest specification for High-bandwidth Digital Content Protection.
- Allows protected content stream to pass between authenticated devices.

Local AC powering – PoE (Power over Ethernet) source

- Supplies industry standard IEEE 802.3af PoE over HDBaseT to an Omega Series, HDVS-200 Series, or AT-UHD-EX-100CE-TX-PD transmitter.
- Allows convenient transmitter installation at any remote location, without the need for local AC power.

Audio de-embedding

- De-embeds two channel PCM audio to a balanced, analog audio output.
- Deliver audio to an amplifier and speakers for sound reinforcement.

Front panel power and signal status LEDs

- LED indicators provide power and HDBaseT link status information.
- Provides convenient setup and troubleshooting.

Low-profile, 1.02 inch (26 mm) high enclosure

- Easy installation into confined spaces below tables, in furniture, and behind or above displays.
- Includes mounting hardware for installation onto surfaces.

Specifications

Video	
Signal	Input - HDMI
Copy Protection	HDCP 2.2
Pixel Clock	300 MHz
HD/SD	4096x2160@60/50/30/25/24Hz 3840x2160@60/50/30/25/24Hz 1920x1080p@60/59.9/50/30/29.97/25/ 24/23.98Hz 1920x1080i@30/29.97/25Hz 1280x720p@60/59.94/50Hz 720x576p@50Hz 720x576i@25Hz 640x480p@60/59.96Hz 640x480i@30Hz
VESA All resolutions are 60Hz	1920x1200 1680x1050 1600x1200 1440x900 1400x1050 1366x768 1360x768 1280x1024 1280x800 1152x768 1024x768 800x600 640x480
Color Space	YUV, RGB
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0
Color Depth	8-bit, 10-bit, 12-bit

Audio			
HDMI Pass-Through Formats	PCM 2.0 LPCM 5.1 LPCM 7.1	Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos®	DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X®
Bit Depth	Up to 24 bits		
Analog Audio			
Format	Stereo 2-Channel		
Output level	L: 5.883 Vrms R: 5.855 Vrms		
Frequency Response	20 Hz to 20 kHz, ± 0.5 dB		
THD+N	< 0.00009% at 20 Hz to 20 kHz		
SNR	> 141.49 dB at 1 kHz		
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz		

Control	
RS-232	2-way device control and monitoring Supported baud rates: 2400, 4800, 9600, 19200, 38400, 57600, 115200
CEC Support	Yes

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI IN/OUT	15	5	30	10
CAT5e	295	90	330	100
CAT6/6a/7	330	100	330	100

Buttons and Indicators

Indicators:	
PWR	1 - LED, green
LINK	1 - LED, yellow

Connectors

HDBaseT IN	1 - RJ45, female
HDMI IN 2	1 - Type A, 19-pin female
VGA IN	1 - Type A, 19-pin female
HDMI OUT	1 - 3-pin captive screw (bidirectional)
AUDIO IN	1 - RJ45, 100Base-T
AUDIO OUT	1 - Mini-USB, 5-pin female
RS-232	1 - 4-pin, mini-DIN locking connector

Environmental

Environmental	Fahrenheit	Celsius
Operating Temperature	+32 to +122	0 to +50
Storage Temperature	-4 to +140	-20 to +60
Operating Humidity (RH)	20% to 90%, non-condensing	

Power

Consumption	15.12 W
External Power Supply	Input: 100 - 240 VAC, 50/60 Hz Output: DC 24 V / 2.7 A

Dimensions (H x W x D)

	Inches	Millimeters
Unit	1.02 x 4.29 x 5.24	26 x 109 x 133
Power Supply (AT-PS-54-C)	1.26 x 1.93 x 4.69	32 x 49 x 119

Weight

	Pounds	Kilograms
Device	0.90	0.41

Certification

Device	CE, FCC
Power Supply	CE, FCC, UL

Compliance

NDAA-899	Yes
TAA	Yes

Accessories

SKU	Description
AT-LC-H2H-1M	LinkConnect HDMI to HDMI Cable
AT-LC-H2H-2M	LinkConnect HDMI to HDMI Cable
AT-LC-H2H-3M	LinkConnect HDMI to HDMI Cable

Copyright, Trademark, and Registration

© 2022 Atлона Inc. All rights reserved. "Atлона" and the Atлона logo are registered trademarks of Atлона Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).