

EN Specifications

Amplifier	DR115DSP	DR112DSP	DR110DSP
Maximum output power	1400 W*	1200 W*	1000 W*
Type	—	Class-D + Class-AB	
Protection	—	Auto-standby, short circuit, open circuit, thermal	
Controls	Rotary push-encoder, input gain controls		
Hardware	Rotary push-encoder, input gain controls		
Loudspeaker/System Data			
Woofer	1 x 15" (381 mm) LF driver	1 x 12" (305 mm) LF driver	1 x 10" (254 mm) LF driver
Tweeter	1 x 1.75" (44.4 mm) HF compression driver	1 x 1.35" (34.4 mm) HF compression driver	
Frequency response	45 Hz – 19 kHz (± 3 dB)	50 Hz – 19 kHz (± 3 dB)	55 Hz – 19 kHz (± 3 dB)
Nominal dispersion	90° H x 60° V		
Maximum SPL	136 dB	134 dB	132 dB
Crossover	2-way, active		
Limiter	Independent HF, LF		
Audio Connections			
Input 1/2	2 x XLR / ¼" TRS combo jacks (servo-balanced)		
Impedance	20 k Ω , balanced / 10 k Ω , unbalanced		
Sensitivity	-26 dBu, nominal		
Max. input level	0 dBu		
Aux in	1 x 1/8" TRS, stereo		
Output	1 x XLR		
Impedance	200 Ω balanced, 100 Ω unbalanced		
Max. output level	-7 dBu		
Digital Signal Processor (DSP)			
Display	LCD 128 x 32, amber backlight		
Factory EQ presets	Music, DJ, Live, Speech		
Equalization	Low, Mid, High		
Bass	± 12 dB @ 80 Hz, shelving		
Middle	± 12 dB @ 2.5 kHz, parametric, Q = 0.5		
Treble	± 12 dB @ 12 kHz, shelving		
Low-cut filter	80 / 100 / 120 / 150 Hz, switchable		
Protection	Lockout function for all settings		
Bluetooth**			
Frequency range	2402 MHz ~ 2480 MHz		

Power Supply/Voltage (Fuses)

USA / Canada / Japan

UK / Australia / Europe / Korea / China

Power consumption @ 1/8 max power

Mains connection

Dimension/Weight

Dimensions (H x W x D)

Weight

*Independent of limiters and driver protection circuits.
 **The Bluetooth® word mark and logos are owned by the