



Technical Specifications



TUBE ULTRAGAIN MIC100

Audiophile Vacuum Tube Preamplifier with Limiter

EN TUBE ULTRAGAIN MIC100**Audiophile Vacuum Tube Preamplifier with Limiter**

- High-end preamplification for all microphone, instrument and line-level sources. Complements especially your studio-grade condenser mics
- Perfectly matches your studio, live and hard disk recording setup
- Hand-selected 12AX7 vacuum tube with UTC technology for exceptional warmth and lowest noise
- Ensures outstanding signal transparency when used as a high-end DI-box
- Sophisticated output limiter prevents the output signal from being distorted
- Eliminates the “dull” sound of standard digital recorders and sound cards
- +48 V phantom power, Phase Reverse switch and 20 dB Pad for utmost flexibility
- Highly accurate 8-segment LED level meter
- Balanced inputs and outputs on ¼" TRS and gold-plated XLR connectors
- 3-Year Warranty Program*
- Conceived and designed by BEHRINGER Germany

Specifications**XLR input**

Connector	Balanced/unbalanced
Type	Transformerless, DC-decoupled input
Impedance	approx. 2 k Ω
Max. input level	+7 dBu / 20 dB with pad

¼" TRS input

Connector	Balanced/unbalanced
Type	Transformerless, DC-decoupled input
Impedance	approx. 1 M Ω
Max. input level	+16 dBu / 20 dB with pad

Audio outputs

Connectors	XLR and ¼" TRS connector balanced/unbalanced
Type	Transformerless, DC-decoupled output
Impedance	approx. 700 Ω balanced / approx. 350 Ω unbalanced
Max. output level	approx. +26 dBu @ 100 k Ω

System specifications

Frequency response	Mic input <10 Hz - 43 kHz (+/-3 dB)
	Line input <10 Hz - 40 kHz (+/-3 dB)

Function controls

Gain	variable (+26 to +60 dB)
Output	variable (-∞ to +10 dB)

Function switches

20 dB pad	Level attenuation (20 dB)
+48 V	Activates the phantom power
Phase reverse	Phase reverse (180°)
Limiter	Limits the output signal

Indicators

Input level	8-segment LED meter: -24, -18, -12, -6, 0, +6, +12, clip
Power-LED	Indicates operation

Power supply**Mains voltages**

USA/Canada	120 V~, 60 Hz, PSU
U.K./Australia	240 V~, 50 Hz, PSU
Europe	230 V~, 50 Hz, PSU
Japan	100 V~, 50 - 60 Hz, PSU

Physical

Dimensions (H x W x D)	64 x 135 x 135 mm (2.5 x 5.3 x 5.3")
Weight (without power supply)	1 kg (2.2 lbs)

*Warranty details can be found at music-group.com.

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH, OR STATEMENT CONTAINED HEREIN. TECHNICAL SPECIFICATIONS, APPEARANCES AND OTHER INFORMATION ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MIDAS, KLARK TEKNIK, LAB.GRUPPEN, LAKE, TANNÖY, TURBOSOUND, TC ELECTRONIC, TC-HELICON, BEHRINGER, BUGERA, DDA AND TC APPLIED TECHNOLOGIES ARE TRADEMARKS OR REGISTERED TRADEMARKS OF MUSIC GROUP IP LTD. © MUSIC GROUP IP LTD. 2015 ALL RIGHTS RESERVED.