

SPECIFICATIONS

Nom / max output levels	Main Mix	+4dBu	+27dBu
	Booth	0dBu	+22dBu
	X:FX Send	0dBu	+20dBu
	Record Out	0dBu	+20dBu

Internal headroom Channels +20dB

Frequency response +/-0.5dB 20Hz - 20kHz

Distortion < 0.05% THD+noise @ 1kHz

Crosstalk < -83dB inter-channel

Residual noise	Mix I	-89dBu
	Booth	-93dBu
	X:FX	-77dBu
	Rec	-92dBu

Mix noise	Mix I	-82dBu
	Booth	-84dBu
	X:FX	-77dBu
	Rec	-87dBu

Channel meters Peak reading 9 LED -20dB to +10dB

Main meters Peak reading 9 LED -20dB to +10dB

Mic EQ 2-Band +/-12dB

Channel EQ 3-Band +6dB / total kill

Channel fader 45mm stereo VCA, < -85dB shutoff

Crossfader 45mm stereo VCA - replaceable

Filters Stereo VCF, analogue

Digital Architecture Specification

Analogue/Digital conversion	24 bit
Analogue/Digital Line-up	+14dBu = 0dBFS
USB soundcard sampling frequency range	44.1kHz to 96kHz

Consumption 30W max

Dimensions and Weights

The console is fitted with rubber feet for desktop operation.

	<u>Width</u>	<u>Height</u>	<u>Depth</u>	<u>Weight</u>
Mixer	320 mm	110mm	370mm	5.2 kg