

W400LVe

Bright projection



- **Bright WXGA projector – 4000 ANSI lumens**
- **Easy connectivity – HDMI, VGA, USB power**
- **Clear, powerful audio - 10W speaker**
- **Lightweight and portable**

Project bright and vibrant presentations effortlessly any time of day in HD. Designed for meeting rooms and classrooms, the W400LVe boasts amazing colour, long lamp life and energy-saving features for a lower overall cost of ownership.

This projector is easy to connect to with multiple inputs, a built-in speaker and USB Power. Perfect for connecting HDMI dongles such as Google Chromecast or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings with the optional carry bag (sold separately).



Specifications

Display/imagen	
Tecnología de visualización	DLP
Resolución	WXGA (1280x800)
Brillo	4,000 lumens
Ratio de contraste	25,000:1
Relación de aspecto nativo	16:10
Ratio de aspecto - compatible	4:3,16:9
Corrección Keystone-Vertical	+/-40°
Frecuencia de muestreo horizontal	15.38 ~ 91.15Khz
Frecuencia de muestreo vertical	50 ~ 85(120 for 3D)Hz
Uniformidad	75%
Tamaño de pantalla	32.24" ~ 299.53" diagonal
Info Lámpara	
Fuente de luz	Lámpara
Vatios lámpara	203
Vida de lámpara (horas)	6000 (Brillante), 12000 (Dinámica), 10000 (Eco), 15000 (Eco+)
Óptica	
Distancia de tiro	1.55:1 ~ 1.73:1
Distancia de proyección (m)	39.37" - 472.44"
Zoom	1.1
Tipo de zoom	Manual
Distancia focal (mm)	21.85 mm~24mm/0.86"~0.945"
Offset nativo	112%
Conectividad	
Conexiones	Entradas 1 x HDMI 1.4a / 3D , 1 x VGA (YPbPr/RGB), 1 x Video compuesto, 1 x Audio 3.5mm Salidas 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232
General	
Nivel sonoro (típico)	27dB
Nivel sonoro (max)	29dB
Compatibilidad PC	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilidad 2D	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Compatibilidad 3D	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
3D	Full 3D
Seguridad	Barra de seguridad, Kensington Lock, Interfaz protegida por contraseña
idiomas OSD / display	25 idiomas: Árabe, Checo, Danés, Holandés, Inglés, Farsi, Finlandés, Francés, Alemán, Griego, Húngaro, Indonesio, Italiano, Japonés, Noruego, Polaco, Portugués, Rumano, Ruso, Chino (simplificado), Español, Sueco, Chino (tradicional), Turco, Vietnamita
Condiciones de funcionamiento	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Control remoto	Mando tipo tarjeta extraplano
Altavoces	1
Wattios por altavoz	10W
Contenido de la caja	AC power cord Remote control Battery Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200
Corriente	
Fuente de alimentación	100 ~ 240V, 50 ~ 60Hz
Consumo energético (standby)	0.5W
Consumo energético (mín.)	187W
Consumo energético (máx.)	225W
Peso y dimensiones	
Dimensiones (W x D x H)	12.44" x 9.61" x 4.25"
Gross weight	9.7 lbs
Net weight	6.61 lbs

