

## CARACTERÍSTICAS TÉCNICAS

CHARACTERISTICS	Low-impedance loudspeaker with 100 V line transformer. Suitable for outdoor use, with IP-66 protection.
POWER	30 W RMS
LOUDSPEAKERS	1 x 4" polypropylene woofer 1x ½" tweeter
RESPONSE	120–20,000 Hz
IMPEDANCE	30 W RMS@100 V (333 ?) 15 W RMS@100 V (667 ?) 7.5 W RMS@100 V (1,333 ?) 3.75 W RMS@100 V (2,667 ?) Baja Z: 8 ?
SENSITIVITY	84 dB at 1 W/1 m
PRESIÓN ACÚSTICA MÁXIMA	98 dB @ máx. W/1 m 87 dB @ máx. W/4 m
ÁNGULO DE COBERTURA	270°@500Hz, 130°@1kHz, 85°@2kHz, 70°@4kHz (-6 dB)
PROTECTION	IP-66 IEC 60068-2-11 Environmental Test (Salt mist)
MATERIAL	Aluminium grille Mount with weathering treatment Stainless steel screws
SWITCH	W selector in high Z and low Z
CONNECTORS	Euroblock
RANGO DE TEMPERATURA	-10°C a 60°C
COLOUR	White (RAL 9003)
DIMENSIONS	125 x 202 x 125 mm depth
WEIGHT	1.7 kg



Amplia la información del producto en:

<https://fonestar.com/ES/SONORA-4TB>